

1 PRELIMINARY EVIDENCE OF COMPLETE STREETS EFFECTS ON BUS
2 OPERATIONS USING AUTOMATED DATA SOURCES

6 **Abubakr Ziedan, Corresponding Author**

7 Graduate Research Assistant
8 Civil & Environmental Engineering
9 University of Tennessee
10 311 John D. Tickle Bldg.
11 851 Neyland Drive
12 Knoxville, TN 37996-2313
13 Tel: 423-364-9229; Email: aziedan@utk.edu

14 **Candace Brakewood, PhD**

15 Assistant Professor of Civil & Environmental Engineering
16 University of Tennessee
17 320 John D. Tickle Bldg.
18 851 Neyland Drive
19 Knoxville, TN 37996-2313
20 Tel: 865-974-7706; Email: cbrakewo@utk.edu

21 **Philip Pugliese, MBA**

22 Chattanooga Area Regional Transportation Authority
23 1617 Wilcox Blvd, Chattanooga, TN 37406
24 Tel: 423-424-1348; Email: philippugliese@gocarta.org

25 Word count: 4,852 words text + 4 tables x 250 words (each) = 5,852 words

30
31
32
33
34
35
36 November 8, 2018

1 ABSTRACT

2 More than 1400 complete streets policies have been adopted in the period from 2004 to 2018
3 nationwide. This proliferation of complete streets policies across the United States has
4 contributed to roadway redesigns and the introduction of bicycle infrastructure to enhance
5 multimodal accessibility. These redesigns often result in a reduction of travel lanes that may
6 affect both motorists and transit operators. This study explored the effects of a complete streets
7 implementation on bus operations using Automated Vehicle Location (AVL) data. A single bus
8 route and corridor in Chattanooga, Tennessee was examined as a case study to assess potential
9 changes in bus speed and reliability following a roadway redesign, road diet, and the introduction
10 of bicycle lanes. This investigation analyzed three periods to perform a comparative analysis
11 between pre- and post-implementation to assess the impact of roadway design changes on bus
12 mean speed and reliability. The findings demonstrate that bus speed was affected significantly in
13 segments where the road design speed or road capacity was reduced, but this impact is limited to
14 the PM peak period only when there was more traffic. The implementation of the complete
15 streets design elements did not significantly affect bus reliability. The results suggest that in areas
16 without significant congestion, complete streets implementation may not have a significant
17 impact on transit operations. As cities continue to implement design features associated with
18 complete streets policies, it will be important to consider the effects of these road changes on bus
19 operations in the long term.

20
21
22
23
24
25 *Keywords:* Complete Streets, Bus Operations, Automatic Vehicle Location Data
26

1 **INTRODUCTION**

2 The complete streets movement over the past two decades has been accompanied by a shift in
3 design focus to balance the needs of all roadway users. Today, more than 1400 complete streets
4 policies have been adopted nationwide (1). The National Complete Streets Collation defines
5 complete streets as “streets for everyone, designed and operated to enable safe access for all
6 users, including pedestrians, bicyclists, motorists and transit riders of all ages and abilities” (2).
7 As streets are designed to accommodate the needs of all road users, the main features of a
8 complete street may include wider and better sidewalks, pedestrian refuge islands, bike lanes,
9 transit lanes, center turn lanes and landscaping (3).

10 The increased number of adopted complete streets policies nationwide is pushing
11 infrastructure changes and shifting the way that planners and engineers are looking at public
12 right-of-way. Prior to the development of the complete streets concept, the priority was often
13 automobile traffic, but now the priority is shifting toward non-motorized modes, including
14 pedestrians and bicycles (3). Although complete streets projects attempt to improve accessibility
15 for different modes of transportation, there is no single design for complete streets (2). Complete
16 streets projects use different designs that can include all or some of the mentioned above
17 features. These different complete streets designs such as road diets often include dedicated bike
18 lanes.

19 Growth in bike ridership nationwide has resulted in more pressure on cities to provide
20 safer and more accessible travel options for cyclists and increased demand for bike infrastructure
21 such as protected bike lanes, regular bike lanes, and greenways. This new bike infrastructure
22 may also affect road capacities in some cases, as public right-of-way is limited and the
23 acquisition of wider right-of-way is expensive in most cases. Therefore, the introduction of new
24 bike infrastructure may result in narrower vehicular lanes or fewer travel lanes. This reduced
25 road capacity may affect the speed, volume and safety of the different road user groups including
26 automobile traffic and public transit vehicles.

27 In light of these trends, this study provides preliminary evidence of the effects of a
28 complete streets implementation on bus operations using automated data sources considering a
29 single bus route in Chattanooga city as a case study. This paper proceeds as follows: first, prior
30 research about complete streets implementation and the effects of road diets presented; the
31 following section provides the objectives of this study; the next section provides background
32 about the case study; data analysis and results follow this section; and the final section is
33 conclusions and future research.

35 **LITERATURE REVIEW**

36 Many studies have evaluated the effects of complete streets policies and road diets on road user's
37 safety, motorists' behavior, and traffic operations. The following review highlights key examples
38 and findings of this research.

39 Smart Growth America (SGA) evaluated 37 complete streets projects nationwide. This
40 evaluation showed that in most cases, there were more walking trips, more bike trips, more
41 transit trips, and fewer vehicular collisions. These findings indicate that complete streets can
42 provide safer streets and increase multimodal travel. However, automobile traffic volumes did
43 not follow a consistent trend as the vehicular flow increased in 13 of these projects and decreased
44 in 19 other projects (4).

45 Gates et al. (2007) provided an evaluation for the safety and operational effects of road
46 diet conversions in Minnesota using speed and crash data for nine sites in Minnesota. These nine
47 sites had Average Daily Traffic (ADT) ranging from 8,300 to 17,400 vehicles per day. This

1 study revealed that the number of total crashes was reduced by 44.2 percent for all sites where
2 there was available crash data. This study also found a reduction in the mean speed and 85th
3 percentile speed. However, these reductions were minor, and they were not expected to have a
4 significant impact on traffic operations. It was recommended that center two-way left turn lanes
5 (TWLTL) be used in roads with ADT less than 17,500 and a speed limit less than 40 mph. It is
6 worth noting that this study did not address any impacts of road diets on transit operations (5).

7 Provence (2009) evaluated the impacts of the 25th Avenue road diet in San Francisco
8 after a year of operation, and this study considered the effects on public transit. This road diet
9 converted 25th Avenue from four lanes to two wide lanes with a two-way central turning lane.
10 The evaluation revealed that the average bus trip length along this corridor was reduced by 6%,
11 and the variation in bus travel times was reduced (6). The buses benefited from using 13'6" wide
12 lane instead of 9 ft. lane and the reduced automobile traffic after the road diet. However, this
13 road diet resulted in 13'6" wide travel lanes, which might not be achievable when introducing
14 bike lanes. Furthermore, this study did not show how this change affected bus on-time
15 performance.

16 These studies revealed various effects of complete streets and road diets, but there is
17 limited prior research on the impact of complete streets implementation on bus operations. This
18 study aims to begin to fill this gap in the literature.
19

20 **OBJECTIVES**

21 The objective of this study is to explore the potential effects of complete streets implementation
22 on bus operations using Automatic Vehicle Location (AVL) data. Specifically, this analysis used
23 bus route #4 in Chattanooga, Tennessee as a case study to evaluate the changes in bus speed and
24 reliability along a corridor that was redesigned after the city of Chattanooga adopted a complete
25 streets policy. This complete streets implementation included the introduction of dedicated bike
26 lanes and the reduction in vehicle lanes along some sections of the bus route under study.
27

28 **BACKGROUND**

29 Chattanooga, Tennessee, is a mid-sized city with an estimated population of 179,139 (7). The
30 city of Chattanooga adopted a complete streets policy by city ordinance in April, 2014 (8).
31 Through this policy, the city of Chattanooga is committed to approach every transportation
32 improvement project with the purpose to create safer, more accessible streets for all users (8).

33 Following adoption of this policy, the city of Chattanooga redesigned two streets:
34 Brainerd Road and Martin Luther King, Jr. Boulevard (MLK Blvd.). The Annual Average Daily
35 Traffic (AADT) was reported in 2016 as 26,999 and 12,481 vehicles per day for Brainerd Road
36 and MLK Blvd., respectively (9). This redesign recommended implementation of a combination
37 of bike infrastructure that included bike lanes and shared lane striping along Brainerd Road and a
38 road diet on MLK Blvd. The redesign recommended bike infrastructure and pavement
39 resurfacing on Brainerd Road on a segment of 1.87-miles from Seminole Drive to Moore Road
40 associated with 5-MPH reduction in the speed limit in part of this segment. The MLK Blvd. road
41 diet was recommended on a 2.6-mile segment from Georgia Avenue to Dodds Avenue, changing
42 it from four lanes to three lanes with a two-way left turn lane. Bike lanes were also proposed on a
43 segment of MLK Blvd. (Figure 1).

44 The city of Chattanooga implemented the earlier mentioned bike infrastructure in
45 December 2017 for Brainerd Road and in April 2018 MLK Blvd. However, the segment on
46 MLK Blvd. that was implemented in April 2018 was only one mile from Georgia Avenue to
47 Central Avenue (Figure 1).




1 The implementation of the proposed bike infrastructure and road diet was expected to
2 affect bus route #4. Bus route #4 connects downtown Chattanooga to Hamilton Place mall,
3 which is the largest shopping mall in the city of Chattanooga. Bus route #4 is the busiest route in
4 the Chattanooga Area Regional Transportation Authority (CARTA) network with a headway of
5 15-minutes from 05:00:00 until 18:30:00 and 30 minute headways after that on weekdays. The
6 outbound direction of bus route #4 runs from downtown Chattanooga along MLK Blvd.,
7 Brainerd Road, Lee Highway and Shallowford Road to the end of the route at Hamilton Place
8 mall. The inbound direction travels along McCallie Avenue towards downtown instead of MLK
9 Blvd. (Figure 1). The previously mentioned bike infrastructure along Brainerd Road affected bus
10 route #4 in both directions (inbound and outbound). For the MLK Blvd road diet, only the
11 outbound direction of bus route #4 was affected.

12 There are five timepoints in each direction of bus route #4, which are shown in Figure 1.
13 Timepoints are public transit stops along routes for which transit vehicles are scheduled to pass
14 at specific time (10). Transit providers typically measure on-time performance at these locations
15 to evaluate transit system performance. For the outbound direction of bus route #4, the impacted
16 section on MLK Blvd. is located between the 4th & Market timepoint and the Bailey & Willow
17 timepoint, while the Brainerd Road bike infrastructure are located before and after Brainerd &
18 Germantown timepoint (Figure 1). For the inbound direction of bus route #4, the Brainerd Road
19 bike infrastructure is located before and after Brainerd & Germantown timepoint, similar to the
20 outbound direction (Figure 1). This study assesses the impacts of the bike infrastructure and the
21 road diet on bus operations for both directions of bus route #4.
22


MLK Blvd. Before Road Diet



MLK Blvd. After Road Diet



Brainerd Road Before Bike Infrastructure



Brainerd Road After Bike Infrastructure

1 DATA ANALYSIS

2 Public transportation providers have benefited from Intelligent Transportation Systems (ITS) to
3 collect data to evaluate their operational performance and provide real-time information to transit
4 users. Automated Vehicle Location (AVL) is one the most common types of ITS technologies
5 used by transit providers to evaluate operating performance like schedule adherence, headway
6 regularity, service reliability, and bus bunching (11). AVL systems can provide data at the stop
7 level, which offers the opportunity for transit agencies to conduct in-depth investigations of their
8 system and track the effect of different changes. This study used CARTA's AVL data to evaluate
9 the effects of complete streets implementation on bus operations in Chattanooga.

10 Period of Analysis

11 Three periods were selected to perform a comparative analysis. Each of these analysis periods is
12 five consecutive weekdays, as follows:

- 15 1. *Before period*: the weekdays 23-Oct to 27-Oct 2017 were selected to represent the base
case scenario prior to any changes;
- 16 2. *After period 1*: the weekdays 22-Jan to 26-Jan 2018 were selected to represent after the
Brainerd Road bike infrastructure implementation;
- 17 3. *After period 2*: the weekdays 18-Jun to 22-Jun 2018 were selected to represent after both
the Brainerd Road bike infrastructure and MLK Blvd. road diet implementation.

21 None of the selected days were holidays or major events. In addition, these analysis
22 periods were chosen at least one month after the implementation of each of the changes to allow
23 time for road users to adapt.

25 Measures

26 For each of the analysis periods, the following data were extracted from CARTA's database for
27 bus route #4:

- 30 • **On-Time Performance (OTP).** These data were extracted for both directions, and it
31 shows the number of on-time, early, and late trips by timepoint. CARTA's database
32 marks an on-time trip if it arrives at the timepoint within the range less than one minute
33 before the scheduled time and no later than five minutes after the scheduled time.
- 34 • **Segment running time.** These data were extracted by trip for both directions. This shows
35 the scheduled and actual running time per segment.
- 36 • **Timepoint arrival time.** This shows the actual arrival time of a vehicle at each
37 timepoint; it is used to calculate the actual headway.
- 38 • **Headway reliability.** This measure shows the percentage of bunched trips, gapped trips,
39 and trips spaced acceptably for each direction. CARTA marks a 'Gap' if the actual
40 headway exceeds the scheduled headway and a 'Bunch' if the actual headway is less than
41 90% of the scheduled headway.

42 Using these data, additional performance measures were calculated. For each of these
43 operational periods, the mean speed per segment was calculated by dividing the segment length
44 by average running time. Percent OTP was calculated as the number of on-time trips divided the
45 total number of trips. The headway coefficient of variation was calculated by dividing the
46 standard deviation of headways by the average headway (12).

1 After performing these calculations, four measures were selected for comparison
2 between the three analysis periods (before period; after period 1; and after period 2) four
3 different operational periods (AM peak from 05:00:00 to 08:59:59; midday from 09:00:00 to
4 14:59:59; PM peak from 15:00:00 to 18:59:59; and evening from 19:00:00 to midnight) for each
5 direction of bus route #4. The four selected performance measures were mean segment speed,
6 percent OTP by timepoint, headway reliability, and headway coefficient of variation. For mean
7 segment speed and OTP by timepoint, T-tests were conducted at a confidence level of 95% to
8 assess the statistical significance between the different analysis periods.
9

10 RESULTS

11 The results of this analysis are divided into two sections. The first section focuses on bus mean
12 speed per segment and how it is affected by the implemented road changes. The second section
13 compares three measures of reliability of bus route #4 before and after the road changes: percent
14 OTP by timepoint, headway reliability, and headway coefficient of variation.
15

16 Speed

17 The mean speed per segment was compared for the three analysis periods (before period; after
18 period 1; after period 2) for the different operational periods (AM peak; midday; PM peak; and
19 evening). There were no statistically significant changes in the AM peak, midday, and evening
20 operational periods (results not shown). However, there were some statistically significant
21 changes for mean speed per segment in PM peak period.

22 For the outbound direction of bus route #4, there was a statistically significant decrease
23 in the speed in the segment between the Bailey & Willow timepoint and the Brainerd &
24 Germantown timepoint after implementing the Brainerd Road bike infrastructure. This
25 statistically significant decrease is likely due to the reduction of the speed limit by 5 MPH in this
26 segment of Brainerd Road after implementing the Brainerd Road bike infrastructure (Table 1).
27 Along with this noticeable decrease in Bailey & Willow to Brainerd & Germantown segment
28 mean speed, there was a statistically significant increase in the mean speed in the segment
29 between the Brainerd & Walmart timepoint and the Hamilton Place mall timepoint (Table 1). It
30 appears that the operators were trying to “catch up” in the last segment of this route.

31 After the MLK Blvd. road diet, there was a speed decrease by about 0.7 MPH in bus
32 mean speed in the segment between the Market & 4th timepoint and the Bailey & Willow
33 timepoint (Table 1). The reduction in bus mean speed in this section was a statistically significant
34 decrease. However, similar to Brainerd Road, it seems that bus operators drove faster in the other
35 segments, which was likely to achieve similar levels of on-time performance.

36 This finding about speed is different from what was reported by a previous study
37 evaluating a road diet in San Francisco; the San Francisco study showed that after a road diet,
38 bus travel times were reduced, which means that speed was increased (6). However, the road diet
39 in San Francisco had buses using 13'6" lanes instead of 9 ft. lanes, which helped to increase the
40 speed. In this case study, the lane width remained 10 ft. before and after the road diet.
41

1 **TABLE 1 Outbound Direction Mean Speed Comparison - PM Peak Period**

| Segment | Mean Speed (MPH) | | | | | | | | |
|--|------------------------------------|---------|------------|------------------------------------|---------|------------|-------------------------------------|---------|------------|
| | Before Period vs After Period 1 | | | Before Period vs After Period 2 | | | After Period 1 vs After Period 2 | | |
| | Before | After 1 | Difference | Before | After 2 | Difference | After 1 | After 2 | Difference |
| Market & 4th to Bailey & Willow (MLK Blvd. road diet) | 11.45 | 11.49 | 0.04 | 11.45 | 10.72 | - 0.73** | 11.49 | 10.72 | - 0.77** |
| Bailey & Willow to Brainerd & Germantown (Brainerd bike infrastructure) | 17.47 | 15.51 | - 1.96** | 17.47 | 16.32 | - 1.15 | 15.51 | 16.32 | 0.81 |
| Brainerd & Germantown to Brainerd & Walmart (Brainerd bike infrastructure) | 14.30 | 14.45 | 0.15 | 14.30 | 14.74 | 0.44 | 14.45 | 14.74 | 0.29 |
| Brainerd & Walmart to Hamilton Mall (Last segment) | 13.35 | 14.27 | 0.92** | 13.35 | 14.50 | 1.15*** | 14.27 | 14.50 | 0.23 |

Significance: * $p < 0.10$; ** $p < 0.05$; *** $p < 0.01$

3 For the inbound direction of bus route #4, there was no clear trend or statistically
 4 significant changes for mean speed in the segments with bike infrastructure in the PM peak
 5 period (Table 2). The only statistically significant changes were in the last segment, where there
 6 was a 0.69 MPH increase in mean speed in Jan-2018 compared to Oct-2017 and a 1.00 MPH
 7 decrease in mean speed in Jun-2018 compared to Jan-2018 (Table 2). Speed changes might be
 8 because June and October have more extended daylight hours than January, which could affect
 9 the traffic patterns in the PM peak period. However, additional investigation for the inbound
 10 direction is needed to provide insight into these unanticipated changes, since there were no road
 11 changes implemented in this segment.
 12

13 **TABLE 2 Inbound Direction Mean Speed Comparison- PM Peak Period**

| Segment | Mean Speed (MPH) | | | | | | | | |
|--|------------------------------------|---------|------------|------------------------------------|---------|------------|-------------------------------------|---------|------------|
| | Before Period vs After Period 1 | | | Before Period vs After Period 2 | | | After Period 1 vs After Period 2 | | |
| | Before | After 1 | Difference | Before | After 2 | Difference | After 1 | After 2 | Difference |
| Hamilton Mall to Brainerd-Walmart | 14.53 | 14.76 | 0.23 | 14.53 | 14.52 | - 0.01 | 14.76 | 14.52 | - 0.24 |
| Brainerd & Walmart to – Brainerd & Germantown (Brainerd bike infrastructure) | 15.85 | 15.48 | - 0.37 | 15.85 | 16.16 | 0.31 | 15.48 | 16.16 | 0.68 |
| Brainerd & Germantown to McCallie & Willow Street (Brainerd bike infrastructure) | 20.88 | 20.12 | - 0.76 | 20.88 | 21.24 | 0.36 | 20.12 | 21.24 | 1.12 |
| McCallie & Willow Street to Market & 4th (Last segment) | 9.82 | 10.51 | 0.69** | 9.82 | 9.51 | - 0.31 | 10.51 | 9.51 | - 1.00** |

Significance: * $p < 0.10$; ** $p < 0.05$; *** $p < 0.01$

1 **Reliability**

2 Three measures were selected to evaluate the effects of complete streets policy implementation
 3 on bus reliability: percent OTP by timepoint, headway reliability, and headway coefficient of
 4 variation for both directions of bus route #4. The main findings of these three reliability
 5 measures are highlighted below.

6 *Timepoints Percent OTP*

7 For the outbound direction, there were no statistically significant changes between the different
 8 analysis periods (Table 3). The observed differences were small variations and do not provide
 9 any evidence of bus OTP changes associated with the Brainerd Road bike lanes and the MLK
 10 Blvd. road diet. Furthermore, the difference in OTP between these analysis periods at the
 11 Hamilton Place mall timepoint was always less than 1% (Table 3). This minimal change in the
 12 percent of on-time trips at the last timepoint supports the assumption that operators drove in
 13 manner such that they would arrive on-time at the last timepoint of the outbound direction of bus
 14 route #4.

16 **TABLE 3 Outbound Direction Timepoints - On-Time Performance Comparison**

| Timepoint | OTP (%) | | | | | | | | |
|-----------------------|------------------------------------|---------|------------|------------------------------------|---------|------------|-------------------------------------|---------|------------|
| | Before Period vs After Period 1 | | | Before Period vs After Period 2 | | | After Period 1 vs After Period 2 | | |
| | Before | After 1 | Difference | Before | After 2 | Difference | After 1 | After 2 | Difference |
| Market & 4th | 81.10 | 79.44 | - 1.66 | 81.10 | 76.72 | - 4.38 | 79.44 | 76.72 | - 2.72 |
| Bailey & Willow | 68.15 | 74.10 | 5.95 | 68.15 | 74.79 | 6.64 | 74.10 | 74.79 | 0.69 |
| Brainerd & Germantown | 63.87 | 70.08 | 6.21 | 63.87 | 67.92 | 4.05 | 70.08 | 67.92 | - 2.16 |
| Brainerd & Walmart | 80.21 | 78.72 | - 1.49 | 80.21 | 72.21 | - 8.00 | 78.72 | 72.21 | - 6.51 |
| Hamilton Mall | 96.49 | 96.46 | - 0.03 | 96.49 | 96.64 | 0.15 | 96.46 | 96.64 | 0.18 |

19 *Significance: * p<0.10; ** p<0.05; *** p<0.01*

20 For the inbound direction, there was a statistically significant improvement for OTP at
 21 the Brainerd & Germantown and McCallie & Willow timepoints between Oct-2017 and Jan-
 22 2018. (Table 4). One possible cause for these improvements in OTP could be long-term effects
 23 of the road resurfacing associated with Brainerd Road bike infrastructure. However, more
 24 analysis periods should be considered to confirm if this improvement is due to long-term effects
 25 of resurfacing or if it is due to other factors, since there were no clear trends for the mean speed.

26 Additionally, there was a statistically significant OTP increase at the Brainerd &
 27 Walmart timepoint from Jan-2018 to Jun-2018; however, there were not any road changes
 28 implemented in the segment between the Hamilton Place mall timepoint and the Brainerd &
 29 Walmart timepoint (Table 4). This unexpected improvement confirms the need for other analysis
 30 periods to conduct in-depth investigation for the inbound direction OTP to find out if these
 31 changes are related to road resurfacing or not.

1 TABLE 4 Inbound Direction Timepoints - On-Time Performance Comparison

2

| Timepoint | OTP (%) | | | | | | | | |
|-----------------------|---------------------------------|---------|------------|---------------------------------|---------|------------|----------------------------------|---------|------------|
| | Before Period vs After Period 1 | | | Before Period vs After Period 2 | | | After Period 1 vs After Period 2 | | |
| | Before | After 1 | Difference | Before | After 2 | Difference | After 1 | After 2 | Difference |
| Hamilton Mall | 83.23 | 82.69 | - 0.54 | 83.23 | 77.67 | - 5.56 | 82.69 | 77.67 | - 5.02 |
| Brainerd & Walmart | 86.18 | 81.90 | - 4.28 | 86.18 | 89.44 | 3.26 | 81.89 | 89.44 | 7.55* |
| Brainerd & Germantown | 72.54 | 75.23 | 2.69 | 72.54 | 81.48 | 8.94** | 75.23 | 81.48 | 6.25 |
| McCallie & Willow | 67.21 | 68.95 | 1.74 | 67.21 | 74.13 | 6.92* | 68.95 | 74.12 | 5.17 |
| Market & 4th | 78.41 | 83.18 | 4.77 | 78.41 | 79.57 | 1.16 | 83.18 | 79.57 | - 3.61 |

Significance: * $p < 0.10$; ** $p < 0.05$; *** $p < 0.01$


3

4 Headway Reliability

5 This section considers headway reliability, which is measured as the percent of bunched trips,
6 gapped trips, and acceptably spaced trips for each analysis period.

7 For the outbound direction, the acceptably spaced trips were 51.86 %, 55.43% and
8 52.79 % of the total trips for Oct-2017, Jan-2018 and Jun-2018, respectively (Figure 3). The
9 percentages of bunched trips and gapped trips were also comparable (Figure 3). These
10 comparable percentages show that there was no major impact for these road changes on headway
11 reliability for the outbound direction.

12 Similar to the outbound direction, the percentage of trips with acceptable spacing were
13 52.31%, 56.78% and 55.05% for Oct-2017, Jan-2018 and Jun-2018, respectively (Figure 3).
14 These results demonstrate that bike infrastructure on Brainerd Road did not have a noticeable
15 effect on headway reliability for the inbound direction of bus route #4. These outcomes imply
16 that headway reliability is likely not affected by these road changes in the short term.



18 FIGURE 2 Bus Route #4 Headway Reliability

19

1 *Headway Coefficient of Variation*

2 The last reliability measure used in this study was headway coefficient of variation. Headway
3 coefficient of variation is a commonly used performance measure for high frequency transit
4 service (12). Although the peak period headway is 15 minutes for bus route #4 (which is greater
5 than the typical threshold of headways of 10 minutes or less for high frequency routes), this
6 measure was used to provide additional insight into the level of reliability.

7 The change in headway coefficient of variation for the outbound direction did not
8 follow a trend for both directions of bus route #4 (results not shown). This confirms that both
9 Brainerd Road bike infrastructure and MLK Blvd. road diet did not have a noticeable effect
10 bunching for both directions.

11 These three measures of reliability – OTP, headway reliability, and headway coefficient
12 of variation – provide early evidence that bus reliability for this route was not significantly
13 affected by the Brainerd Road bike infrastructure and the MLK Blvd. road diet.

14

15 **CONCLUSIONS AND FUTURE RESEARCH**

16 As more complete streets policies are adopted nationwide, the demand for multimodal roads is
17 increasing. Providing roadway space for non-motorized modes affects both traffic and transit
18 operations. Although prior studies have evaluated different impacts of complete streets
19 implementation, there are a limited number of studies considering the impacts on transit
20 operations. This study evaluates a single bus route and corridor in Chattanooga, Tennessee as a
21 case study to assess potential changes in bus speed and reliability following a roadway redesign,
22 road diet, and the introduction of bicycle lanes.

23 This analysis shows that after implementing bike infrastructure on Brainerd Road, the
24 only segment impacted significantly was in the middle of the route. A reduction in bus mean
25 speed in this segment was expected since the speed limit was reduced by 5-MPH after
26 implementing bike infrastructure. Furthermore, after the MLK Blvd. road diet, the bus mean
27 speed in the first segment had a statistically significant decrease of 0.7 MPH in the PM peak
28 period. There was also a statistically significant increase in the mean speed in the last segment,
29 which was likely because bus operators appear to be trying to reach the end of the route on time.
30 These findings suggest that changes in roadway design speed and reductions in travel lanes affect
31 bus speeds.

32 The second part of the analysis focused on the impacts of complete streets
33 implementation on bus reliability. This part of the analysis shows that although the bus mean
34 speed decreased significantly in the affected segments after implementation of the Brainerd Road
35 bike infrastructure and the MLK Blvd. road diet, on-time performance (OTP) was not
36 significantly affected and the operators were able to attain the similar levels of OTP after these
37 road changes. Assessment of headway reliability showed that bunching percentages were similar
38 before and after analysis periods, indicating that bunching was not affected by the Brainerd Road
39 bike infrastructure or MLK Blvd. road diet in the short term. The change in headway coefficient
40 of variation between these analysis periods did not follow a clear trend, which suggests that
41 headway coefficient of variation was not affected by the bike infrastructure and the road diet.
42 Taken together, these three reliability measures imply that levels of reliability on bus route #4
43 were not impacted in the short term.

44 In summary, this study provides preliminary evidence that road diets have limited
45 impact on bus speeds and reliability in the short term. However, it is important to note that the
46 buses considered in this study were operating in areas without high levels of congestion from
47 vehicular traffic and that only a short time period had passed after the implementation of the

1 infrastructure changes. Future work should investigate the long-term effects of complete streets
2 implementation on bus operations. Specific to Chattanooga, it would be useful to analyze
3 additional time periods in the future to investigate the unpredictable changes in the inbound
4 direction of bus route #4. In addition, similar evaluations should be conducted for different
5 complete streets projects in other regions on roads with different levels of vehicular traffic; this is
6 likely to be a fruitful area for future research in light of the increasing number of complete streets
7 projects throughout the country.

9 **AUTHOR CONTRIBUTION STATEMENT**

10 The authors confirm contribution to the paper as follows: study conception and design: A.
11 Ziedan, C. Brakewood, P. Pugliese; data collection: A. Ziedan; analysis and interpretation of
12 results: A. Ziedan, C. Brakewood, P. Pugliese; draft manuscript preparation: A. Ziedan, C.
13 Brakewood, and P. Pugliese. All authors reviewed the results and approved the final version of
14 the manuscript.

15 **REFERENCES**

- 17 [1] *National Complete Streets Coalition | Smart Growth America.*
18 <https://smartgrowthamerica.org/program/national-complete-streets-coalition/>. Accessed 07/18/2018.
- 19 [2] *What are Complete Streets? | Smart Growth America.*
20 <https://smartgrowthamerica.org/program/national-complete-streets-coalition/publications/what-are-complete-streets/>. Accessed 07/10/2018.
- 22 [3] Litman, T. Evaluating complete streets: The value of designing roads for diverse modes, users and
23 activities, Victoria Transport Policy Institute, 2012.
- 24 [4] *Safer Streets, Stronger Economies: Complete Streets Project Outcomes from Across the Country.*
25 Smart Growth America. <https://smartgrowthamerica.org/resources/evaluating-complete-streets-projects-a-guide-for-practitioners/>. Accessed 07/01/2018.
- 27 [5] Gates, T., D. Noyce, V. Talada, and L. Hill. The safety and operational effects of “road diet”
28 conversions in Minnesota. Presented at 86th Annual Meeting of the Transportation Research
29 Board, Washington, D.C., 2007.
- 30 [6] Provence, D. 25th Avenue Road Diet Project: A One Year Evaluation, The San Francisco Municipal
31 Transportation Agency, 2009.
- 32 [7] *U.S. Census Bureau Quick Facts: Chattanooga city, Tennessee.*
33 <https://www.census.gov/quickfacts/fact/table/chattanoogacitytennessee/PST045217>. Accessed
34 07/10/2018.
- 35 [8] *An Ordinance to Amend Chattanooga City Code.* <http://chattanooga.gov/city-council-files/OrdinancesAndResolutions/Ordinances/Ordinances%202014/12822%20City%20Code%2032%20-%20Complete%20Streets%20Definitions.pdf>. Accessed 07/18/2018.
- 38 [9] *TDOT Traffic History.* <https://www.tdot.tn.gov/APPLICATIONS/traffichistory>. Accessed 07/19/2018.
- 39 [10] Ceder, A. *Public transit planning and operation: Modeling, practice and behavior.* CRC press, 2007.
- 40 [11] Hammerle, M., M. Haynes, and S. McNeil. Use of automatic vehicle location and passenger count
41 data to evaluate bus operations. *Transportation Research Record: Journal of the Transportation Research
42 Board*, No. 1903, 2005, pp. 27-34.
- 43 [12] Kittelson & Assoc, I., Parsons Brinckerhoff, Inc., KFH Group, Inc., Texam A&M Transportation
44 Institute, & Arup. TCRP Report 165: Transit Capacity and Quality of Service Manual, Transportation
45 Research Board, Washington, D.C., 2013. p. 22.